



### Set content

Model Type	TY-CSP1
Number	1
Carton dimensions	140 mm x 325 mm x 172 mm (5.52" x 12.80" x 6.78")
Gross weight	1600 g (3.53 lbs)
Accessories	USB Type-C to Type-C cable (Approx.1.0 m) USB Type-C to Type-A cable(Approx.1.8 m) AC Adaptor (including 3 conversion plugs)

### PRODUCT SPECIFICATION

(design and specification subject to change without notice)

#### SPECIFICATION

CAMERA		ENVIRONMENTAL	
Camera sensor	1/2.7" 5MP CMOS	Operating Environment	Temperature : 0 °C to 40 °C (32 °F to 104 °F) Humidity : 20% to 80% (Non condensation)
Shooting pixels	2560 x 1440 x 4	Usable altitude range	0 m to 2800 m / 0 ft to 9186 ft
Panorama resolution and frame rate	5K (4992 x 928) @25/30fps	UPC Code	885170391277
Output resolution and frame rate	720 x 480 @ 25/30fps 1920 x 1080 @ 25/30fps 3840 x 640 / 960 @ 25/30fps	Features	
Viewing angle	360 (H) x 60 (V)	Video display modes (View)	Single / Dual / Multi / Surround / Stable
Camera units	4	The operation of button	Changing Mode / Adjustment of volume / Audio mute
Lens FOV (Field of view)	140 (D) / 140 (H) / 103 (V)	Application	PressIT360 application Support OS : Microsoft Windows (Windows 10/Windows 11), / macOS
F number of the lens	2.5		
Lens TTL	14.7 mm (0.58")		
Opt Distortion	<-14.9 %		
Video format	Motion JPEG		
USB video format	UVC Revision 1.5		
MIC			
Microphone	MEMS microphone array		
MIC units	7		
Beam forming	Supported		
MIC sensitivity	-35 dBFS		
SN ratio	68.75 dBA		
MIC pick up distance	Up to 5 m (16.4 ft)		
SPEAKER			
Speaker out	1.5 W (When supplying power from USB Type-C) or 3 W (When AC adaptor is connected)		
Noise canceling	AEC/AGC/DNR/Keyboard noise suppression		
USB sound format	UAC Revision 1.0		
TERMINALS			
USB	USB Type-C (USB2.0)		
Power	DC plug		
ELECTRICAL			
Power	USB Type-C (5 V/3 A) or AC adaptor DC 12 V/2 A		
Power consumption (when outputting video)	11W		
MECHANICAL			
Dimension (Diameter x Height)	φ 64 mm (2.52") x 285 mm (11.23") (Operation base φ 100 mm (3.94"))		
Weight	950 g/2.1 lbs		
Color	black		
Security slot	Noble Wedge lock (with mounting surfaces of 11 mm φ or less.)		

**DIMENSIONS**

Units : mm [inch]

